

Excellent Security RC Lipo Battery 5000mah 11.1 Volts 3S 60C With W/XT-90

Our Product Introduction

for more products please visit us on lohuite.com

Basic Information

- Place of Origin: Guangdong, China
- Brand Name: lohuite
- Model Number: 5000mah
- Minimum Order Quantity: 2 packs
- Price: \$28.30/packs 2-49 packs
- Packaging Details: as export package
- Supply Ability: 100000 Pack/Packs per Week



Product Specification

- Weight: 440g
- The Discharge Rate: 11.3~11.8V(cell 3.8~3.9V)
- Storage Type: 0 ~40
- Nominal Capacity: 5000mAh
- Nominal Voltage: 11.1V
- Operating Temperature: Charging: 0 ~40
- Constant Discharge Current: Constant Current 20C End Voltage18.0V
- Port: Hk
- Highlight: **Lipo Battery 5000mah 11.1 Volts,
Excellent Security RC Lipo Battery ,
W/XT-90 RC Lipo Battery**

Product Description

RC Car Lipo Battery 11.1v Heavy Duty 5000mAh 3S 60C Lipo Pack w/XT-90

Spec.

Capacity: **5000mAh**

Configuration: **3S1P / 11.1v / 3Cell**

Constant Discharge: **60C / 120C (Burst)**

Weight: **440g**

Dimension: **(L)144 x (W)51 x (H)30mm**

Balance Plug: **JST-XH**

Discharge plug: **XT90**

Wire Gauge: **10AWG**

Please note: This pack is compatible with the following popular models, you may require a connector change or a plug adapter.



Application



Drones



RC Cars



RC Boat



RC Helicopters



FPV Racing



RC Airplane

Amass Connector

★ Other connector if you need, please feel free contact me, thanks



XT90



XT60



XT90-S



T/Deans



EC5



XT150



XT150+AS150



EC3



- 22.2V 10000mAh 25C lipo battery for quadcopter DJI S1000 S800 S800EVO E1100-V2
- 1.Stable automatical stacking technology makes the single cell capacity can reach larger capacity.
 - 2.The most strict single cell capacity, voltage, resistance, discharge curve matching process.
 - 3.Superior Japan and Korea Lithium Polymer raw materials.
 - 4.Almost 200Wh/kg energy density.
 - 5.At least 500 times cycle life.

Our advance:

1. Long Cycle Life

Up to 500 times attested through long production inspection and clients' chase record

2.Low Self-discharge

When placing and idling the battery 7 days at temperature of 50oC, the self-discharge is lower than 15%. 28 days in the room temperature , dischageness itself is inferior to 20%

3.High Rate Charging and Discharging

High rate capacity as the ultimate testing standard before leaving the factory,dynamic battery dischades in 10c, the performanc e is up to IEC standard.

4. Superior Over-charge Endurance

The low internal pressure in charging eliminates the leakage

5. Consistency

All the processes are under the strict quality control in accordance with ISO9002, including the capacity, internal resistance, discharge platform, self-discharge and the special thermostat treatment. This ensures the assembly factory to assemble the packs without any trouble.



Shenzhen Lohuite Technology Co., Ltd.



15007080727



shenzhen@longyun.xyz



lohuite.com

4105, Unit 1, Building B, No. 999 Meilong Avenue, Jingxin Community, Longhua Street, Longhua District, Shenzhen