High Output 1050mAh 14.8V 4s1P Lipo Battery 130C RC Model Boat Batteries

Basic Information

- Brand Name:
- lohuite
- Model Number: • Minimum Order Quantity:
- Price:
- Packaging Details:
- Supply Ability:
- **2S LIPO BATTERY**
- \$16.90/packs 1-49 packs

1

- as export package
 - 100000 Pack/Packs per Week



Product Specification

 Highlight: 	High Output 4s1P Lipo Battery, 14.8V RC Model Boat Batteries, 4s1P Lipo Battery 130C
• SIZE:	22*38*78mm
 Suggest Charge Rate: 	1C (Max 5C)
 Discharge Rate: 	130C-260C
 Voltage Per Pack: 	14.8V
• Cells:	4s
Capacity:	1050mah
 Storage Type: 	0-45
• The Discharge Rate:	14.8v-15.3V
 The Charging Ratio: 	14.8V
• Weight:	132g



1050mAh 14.8V 4s1P Lipo batteries 130C RC Boat battery

Product Description





Capacity	Size(mm)	Weight
2S 2200mah 50C	88x34x20	114g=4oz=0.25lb
2S 2600mah 30C	115x34x17	131g=4.62oz=0.28lb
2S 5000mah 50C	155x48x16	260g=9.17oz=0.57lb
2S 6000mah 60C Hard	138x46x24	295g=10.4oz=0.65lb
2S 7000mah 55C Hard	138x46x24	312g=11oz=0.68lb
3S 1500mah 65C	70x43x22	125g=4.4oz=0.27lb
3S 1500mah 100C	90x34x22	141g=4.97oz=0.31lb
3S 1800mah 50C	105x34x20	142g=5oz=0.31lb
3S 2200mah 30C	106x34x24	168g=5.92oz=0.37lb
3S 2600mah 35C T	115x34x26	189g=6.66oz=0.41lb
3S 3000mah 60C	135x42x21	225g=7.93oz=0.49lb
3S 5000mah 50C	155x48x24	376g=13.26oz=0.86lb
3S 6000mah 50C	155x44x29	425g=14.99oz=0.93lb
3S 6000mah 50C Hard	138x46x39	425g=14.99oz=0.93lb
4S 1500mah 100C	70x43x29	164g=5.78oz=0.36lb
4S 2200mah 30C	106x34x32	220g=7.76oz=0.48lb
4S 3300mah 60C	135x42x30	318g=11.21oz=0.7lb
4S 4000mah 60C	135x42x33	403g=14.21oz=0.88lb
4S 5000mah 50C	155x48x32	492g=17.35oz=1.08lb
4S 6000mah 50C	155x44x38	558g=19.68oz=1.23lb
6S 1800mah 50C	105x34x40	270g=9.52oz=0.59lb
6S 3300mah 60C	135x42x42	436g=15.37oz=0.96lb
6S 5000mah 50C	155x48x48	725g=25.57oz=1.59lb
6S 6000mah 50C	155x48x54	809g=28.53oz=1.78lb

Specification

item	value
Warranty	1year
Anode Material	Other
Chargeable	Yes
Application	Toys, Power Tools, BOATS FPV
Battery Size	Li-polymer
Brand Name	Lohuite
Model Number	4S LIPO BATTERY
Weight	132g
The charging ratio	14.8V
The discharge rate	14.8-15.3V
Storage Type	0-45
Capacity	1050mah
Cells	4s
Voltage per pack	14.8V
Discharge rate	120C-240C
Suggest chargerr	Balance charge
Suggest charge rate	1C (Max 5C)
Suggest charger	Balance charger
Balancer Connector Type	3PINS JST-XH xt60

Packing & Delivery



Company Profile



Lohuite in manufacturing lithium polymer batteries since 2001 for digital devices,hobbies&toys,gps,medical,military,electric vehiclesetc.have 3 series lipo battery:High energy density,Low temperature and high temperature.
Shenzhen Lohuite Technology Co., Ltd.
S 15007080727 Shenzhen@longyun.xyz lohuite.com
4105, Unit 1, Building B, No. 999 Meilong Avenue, Jingxin Community, Longhua Street, Longhua District, Shenzhen